

Весы стандартные CARL ROTH серии FX, FZ, EK, ADB, ADJ, ABS-N, ABJ-NM, ALJ, PX, PR, HR

Технические характеристики

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Саранск (8342)22-96-24
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тургут (3462)77-98-35
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия (495)268-04-70

Казахстан (772)734-952-31

Киргизия (996)312-96-26-47



Balances - Standard

Precision balances

A & D.

Application:

- Percent, counting and animal weighing
- Selectable weight units: g, ct, etc.



Features:

- FX-i models have external calibration
- FZ-i models have internal calibration
- All models with additional WP: Dust and water protection acc. to IP 65
- Draft shield for models with 0.001 g readability (internal height 85 mm); (W) = incl. draft shield
- With RS 232 data port
- Overload protection
- Four-year warranty

Delivery incl. mains adapter.

FX series models with external calibration

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
FX-120i (W)	122	0,001	±0,002	±0,001	Ø 130	CTH4.1	1 unit(s)	
FX-200i (W)	220	0,001	±0,002	±0,001	Ø 130	CTH6.1	1 unit(s)	
FX-300i (W)	320	0,001	±0,002	±0,001	Ø 130	CTH8.1	1 unit(s)	
FX-1200i	1220	0,01	±0,02	±0,01	Ø 150	CTK0.1	1 unit(s)	
FX-2000i	2200	0,01	±0,02	±0,01	Ø 150	CTK2.1	1 unit(s)	
FX-3000i	3200	0,01	±0,02	±0,01	Ø 150	CTK4.1	1 unit(s)	

FZ series models with internal calibration

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
FZ-120i (W)	122	0,001	±0,002	±0,001	Ø 130	EHP8.1	1 unit(s)	
FZ-200i (W)	220	0,001	±0,002	±0,001	Ø 130	EHP9.1	1 unit(s)	
FZ-300i (W)	320	0,001	±0,002	±0,001	Ø 130	EHT0.1	1 unit(s)	
FZ-1200i	1220	0,01	±0,02	±0,01	Ø 150	EHT1.1	1 unit(s)	
FZ-2000i	2200	0,01	±0,02	±0,01	Ø 150	EHT2.1	1 unit(s)	
FZ-3000i	3200	0,01	±0,02	±0,01	Ø 150	EHT3.1	1 unit(s)	

FX series models with external calibration, dust and water protection acc. to IP 65

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
FX-120i-WP (W)	122	0,001	±0,002	±0,001	Ø 130	CTH5.1	1 unit(s)	
FX-200i-WP (W)	220	0,001	±0,002	±0,001	Ø 130	CTH7.1	1 unit(s)	
FX-300i-WP (W)	320	0,001	±0,002	±0,001	Ø 130	CTH9.1	1 unit(s)	
FX-1200i-WP	1220	0,01	±0,02	±0,01	Ø 150	CTK1.1	1 unit(s)	
FX-2000i-WP	2200	0,01	±0,02	±0,01	Ø 150	CTK3.1	1 unit(s)	
FX-3000i-WP	3200	0,01	±0,02	±0,01	Ø 150	CTK5.1	1 unit(s)	

FX series models with internal calibration, dust and water protection acc. to IP 65

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
FZ-120i-WP (W)	122	0,001	±0,002	±0,001	Ø 130	CTK6.1	1 unit(s)	
FZ-200i-WP (W)	220	0,001	±0,002	±0,001	Ø 130	CTK7.1	1 unit(s)	
FZ-300i-WP (W)	320	0,001	±0,002	±0,001	Ø 130	CTK8.1	1 unit(s)	
FZ-1200i-WP	1220	0,01	±0,02	±0,01	Ø 150	CTK9.1	1 unit(s)	
FZ-2000i-WP	2200	0,01	±0,02	±0,01	Ø 150	CTL0.1	1 unit(s)	
FZ-3000i-WP	3200	0,01	±0,02	±0,01	Ø 150	CTL1.1	1 unit(s)	

Balances - Standard

Precision balances, explosion protected EK series

A & D.

For explosive areas in zones 0.1 and 2.

Application:

- Item counting and percentage weighing
- Acc. to ATEX: II 1G ia IIB T3 Ga
- With external calibration



Features:

- Backlit display, can be deactivated
- Auto power OFF to prolong battery life (battery life approx. 250 h with backlight off)
- Weighing pan made of stainless steel
- Anti-theft lug, level indicator, levelling feet

Delivery incl. 4 x 1.5 V AA batteries. Please note: Use only type-tested replacement batteries (see operating instructions).

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
EK-300AEP	300	0,01	±0,02	±0,01	Ø 110	EXC0.1	1 unit(s)	
EK-3000AEP	3000	0,1	±0,02	±0,01	133 x 170	EXC1.1	1 unit(s)	
EK-12KAEP	12000	1	±1	±1	133 x 170	EXC2.1	1 unit(s)	

Analytical balances ADB/ADJ series

Kern.

Application:

Item counting and percentage weighing

Features:

- Stainless steel weighing platform
- With RS 232 data port
- Dimensions of entire balance incl. draft shield (W):
W 230 x D 310 x H 330 mm
- Weighing space dimensions: W 170 x D 160 x H 205 mm



Delivery incl. mains adapter.

ADB series with external calibration function

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (%)	Weighing pan (mm)	Art. No.	Pack Qty.	
ADB 100-4 (W)	120	0.0001	±0,0004	±0,0002	Ø 90	HPP9.1	1 unit(s)	
ADB 200-4 (W)	210	0.0001	±0,0004	±0,0002	Ø 90	HPT0.1	1 unit(s)	

ADJ series with internal automatic calibration, either after a change of temperature ≥ 2 °C or time-controlled

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (%)	Weighing pan (mm)	Art. No.	Pack Qty.	
ADJ 100-4 (W)	120	0.0001	±0,0004	±0,0002	Ø 90	KHE3.1	1 unit(s)	
ADJ 200-4 (W)	210	0.0001	±0,0004	±0,0002	Ø 90	KHE4.1	1 unit(s)	



Balances - Standard

Analytical balances

Kern.

Application:

- Item counting, percentage weighing and batching
- High stability mode and other filter settings are selectable



Features:

- ABS-N models with external calibration
- ABJ-NM models have internal automatic calibration, either after a change of temperature $>2^{\circ}\text{C}$ or time-controlled every 4 hours
- Spirit level
- Dimensions of entire balance incl. draft shield: W 210 x D 340 x H 325 mm
- Dimensions of weighing space: W 174 x D 162 x H 227 mm; (W) = incl. draft shield

ABS-N series models with external calibration

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
ABS 80-4N (W)	80	0.0001	$\pm 0,0003$	$\pm 0,0002$	$\varnothing 91$	TA63.1	1 unit(s)	
ABS 120-4N (W)	120	0.0001	$\pm 0,0003$	$\pm 0,0002$	$\varnothing 91$	TA64.1	1 unit(s)	
ABS 220-4N (W)	220	0.0001	$\pm 0,0003$	$\pm 0,0002$	$\varnothing 91$	TA65.1	1 unit(s)	
ABS 320-4N (W)	320	0.0001	$\pm 0,0003$	$\pm 0,0002$	$\varnothing 91$	TA66.1	1 unit(s)	

ABJ-NM series models with internal calibration, cannot be calibrated

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
ABJ 120-4NM (W)	120	0.0001	$\pm 0,0003$	$\pm 0,0002$	$\varnothing 91$	TA67.1	1 unit(s)	
ABJ 220-4NM (W)	220	0.0001	$\pm 0,0003$	$\pm 0,0002$	$\varnothing 91$	TA68.1	1 unit(s)	
ABJ 320-4NM (W)	320	0.0001	$\pm 0,0003$	$\pm 0,0002$	$\varnothing 91$	TA69.1	1 unit(s)	

Balances - Standard

Semi-micro and analytical balances ALJ series

Kern.

Application:

Function programs: Item counting, percentage weighing, weighing with a tolerance range, animal weighing function and recipe

Features:

- With internal automatic calibration if temperature changes by ≥ 1.2 °C and time-controlled every 3 hours
- Available with or without an ionizer:
ionizer to neutralise electrostatic charge.
The ionizing blower is activated by pressing a button.
- RS 232 data port
- Dimensions of weighing space with draft shield:
W 160 x D 140 x H 205 mm; (W) = incl. draft shield
- Overall dimensions (incl. draft shield) W 210 x D 340 x H 330 mm



Delivery incl. protective hood.

(1) Standard version

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
ALJ 200-5DA (W)	80/220	0.00001/0.0001	$\pm 0.0001 / 0.0002$	$\pm 0.00004 / 0.0001$	Ø 80	HPT1.1	1 unit(s)	
ALJ 250-4A (W)	250	0.0001	± 0.0003	± 0.0001	Ø 80	HPT2.1	1 unit(s)	
ALJ 310-4A (W)	310	0.0001	± 0.0003	± 0.0001	Ø 80	HPT3.1	1 unit(s)	
ALJ 500-4A (W)	510	0.0001	± 0.0004	± 0.0002	Ø 80	HPT4.1	1 unit(s)	

(1) Standard version, calibrated ex works

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
ALJ250-4AM (W)	250	0.0001	± 0.0003	± 0.0002	Ø 80	1H25.1	1 unit(s)	

(2) Comfort design with ionizer

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
ALJ 200-5DA (W)	80/220	0.00001/0.0001	$\pm 0.0001 / 0.0002$	$\pm 0.00004 / 0.0001$	Ø 80	HPT5.1	1 unit(s)	
ALJ 250-4A (W)	250	0.0001	± 0.0003	± 0.0001	Ø 80	HPT6.1	1 unit(s)	
ALJ 310-4A (W)	310	0.0001	± 0.0003	± 0.0001	Ø 80	HPT7.1	1 unit(s)	
ALJ 500-4A (W)	510	0.0001	± 0.0004	± 0.0002	Ø 80	HPT8.1	1 unit(s)	

Semi-micro, analytical and precision balances Pioneer® series

Ohaus.

Application: item counting, percentage weighing and dynamic weighing

Features:

- Backlit LCD display
- Glass draft shield with 3 sliding doors for models with 0.00001, 0.0001 and 0.001 g readability (internal height 200 mm); (W) = incl. draft shield
- Models with draft shield are fitted with an antistatic rod for grounding (made from permanent static, electrically conductive ABS)
- Spirit level, safety lug
- USB and RS 232 data port

Delivery incl. industrial protective cover and mains adapter.

Models with external calibration, cannot be calibrated

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
PX124 (W)	120	0.0001	± 0.0002	± 0.0001	Ø 90	KAC6.1	1 unit(s)	
PX224 (W)	220	0.0001	± 0.0002	± 0.0001	Ø 90	KAC7.1	1 unit(s)	
PX323 (W)	320	0.001	± 0.002	± 0.001	Ø 120	KAC8.1	1 unit(s)	
PX523 (W)	520	0.001	± 0.002	± 0.001	Ø 120	KAC9.1	1 unit(s)	
PX3202	3200	0.01	± 0.02	± 0.01	Ø 180	KAE0.1	1 unit(s)	
PX5202	5200	0.01	± 0.02	± 0.01	Ø 180	KAE1.1	1 unit(s)	
PX4201	4200	0.1	± 0.2	± 0.1	Ø 180	KAE2.1	1 unit(s)	





Balances - Standard

Models with internal calibration, cannot be calibrated

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
PX125D (W)	52/120	0.00001/0.0001	±0,0001 /0,0001	±0,00002/0,0001	Ø 80	KAÉ3.1	1 unit(s)	
PX85 (W)	82	0.00001	±0,0001	±0,00002	Ø 80	KAÉ4.1	1 unit(s)	
PX225D (W)	82/220	0.00001/0.0001	±0,0001/0,0001	±0,00002/0,0001	Ø 80	KAÉ5.1	1 unit(s)	
PX124 (W)	120	0.0001	±0,0002	±0,0001	Ø 90	KAÉ6.1	1 unit(s)	
PX224 (W)	220	0.0001	±0,0002	±0,0001	Ø 90	KAÉ7.1	1 unit(s)	
PX323 (W)	320	0.001	±0,002	±0,001	Ø 120	KAÉ8.1	1 unit(s)	
PX523 (W)	520	0.001	±0,002	±0,001	Ø 120	KAÉ9.1	1 unit(s)	
PX3202	3200	0.01	±0,02	±0,01	Ø 180	KAH0.1	1 unit(s)	
PX5202	5200	0.01	±0,02	±0,01	Ø 180	KAH1.1	1 unit(s)	
PX4201	4200	0.1	±0,2	±0,1	Ø 180	KAH2.1	1 unit(s)	

Models with internal calibration, calibrated ex works

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
PX125D (W)	52/120	0.00001/0.0001	±0,0001/0,0001	±0,00002/0,0001	Ø 80	KAH3.1	1 unit(s)	
PX85 (W)	82	0.00001	±0,0001	±0,00002	Ø 80	KAH4.1	1 unit(s)	
PX225D (W)	82/220	0.00001/0.0001	±0,0001/0,0001	±0,00002/0,0001	Ø 80	KAH5.1	1 unit(s)	
PX124 (W)	120	0.0001	±0,0002	±0,0001	Ø 90	KAH6.1	1 unit(s)	
PX224 (W)	220	0.0001	±0,0002	±0,0001	Ø 90	KAH7.1	1 unit(s)	
PX323 (W)	320	0.001	±0,002	±0,001	Ø 120	KAH8.1	1 unit(s)	
PX523 (W)	520	0.001	±0,002	±0,001	Ø 120	KAH9.1	1 unit(s)	
PX3202	3200	0.01	±0,02	±0,01	Ø 180	KAK0.1	1 unit(s)	
PX5202	5200	0.01	±0,02	±0,01	Ø 180	KAK1.1	1 unit(s)	
PX4201	4200	0.1	±0,2	±0,1	Ø 180	KAK2.1	1 unit(s)	

Analytical and precision balances PR series

Ohaus.

Application

Item counter, percentage weighing

Features:

- With internal adjustment
- Background LCD
- Stainless steel weighing pan
- Glass draft shield (W) with three sliding doors for models with 0.0001 g and 0.001 g readability (interior height 170 mm); (W) = incl. draft shield
- Safety lug, stability indicator
- RS-232 data port



Models with internal calibration, cannot be calibrated

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
PR224 (W)	220	0.0001	±0,0002	±0,0001	Ø 90	KHH9.1	1 unit(s)	
PR523 (W)	520	0.001	±0,002	±0,001	Ø 120	KHK0.1	1 unit(s)	
PR2202	2200	0.01	±0,02	±0,01	Ø 180	KHK1.1	1 unit(s)	
PR4202	4200	0.01	±0,02	±0,01	Ø 180	KHK2.1	1 unit(s)	
PR4201	4200	0.1	±0,2	±0,1	Ø 180	KHK3.1	1 unit(s)	
PR6201	6200	0.1	±0,2	±0,1	Ø 180	KHK4.1	1 unit(s)	

Models with internal calibration, calibrated ex works

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.	
PR224M (W)	220	0.0001	±0,0002	±0,0001	Ø 90	KHK5.1	1 unit(s)	
PR523M (W)	520	0.001	±0,002	±0,001	Ø 120	KHK6.1	1 unit(s)	
PR2202M	2200	0.01	±0,02	±0,01	Ø 180	KHK7.1	1 unit(s)	
PR4202M	4200	0.01	±0,02	±0,01	Ø 180	KHK8.1	1 unit(s)	
PR4201M	4200	0.1	±0,2	±0,1	Ø 180	KHK9.1	1 unit(s)	
PR6201M	6200	0.1	±0,2	±0,1	Ø 180	KHL0.1	1 unit(s)	

Balances - Standard

Analytical balances HR series

A & D.

Application:

- Percent, counting, animal weighing
- Selectable weight units: g, mg, ct, etc.



Features:

- HR-A model with external calibration
- HR-AZ models with internal calibration
- Backlit LCD display
- Removable, round full-sized draft shield (internal height 198 mm); (W) = incl. draft shield
- The sliding doors of the draft shield tilt back to minimise space requirements
- With RS 232 data port
- Level indicator on the front
- Solid metal housing
- Overload protection
- Four-year warranty

Delivery incl. mains adapter.

Models with external calibration

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.
HR-251A	62 / 252	0,0001 / 0,001	±0,0003 / 0,001	±0,0001 / 0,001	Ø 90	CTE2.1	1 unit(s)
HR-100A	102	0,0001	±0,0002	±0,0001	Ø 90	CTE3.1	1 unit(s)
HR-150A	152	0,0001	±0,0002	±0,0001	Ø 90	CTE4.1	1 unit(s)
HR-250A	252	0,0001	±0,0003	±0,0002	Ø 90	CTE5.1	1 unit(s)

Models with internal calibration

Type	Weighing range (g)	Readability (g)	Linearity (g)	Reproducibility (g)	Weighing pan (mm)	Art. No.	Pack Qty.
HR-251AZ (W)	62 / 252	0,0001 / 0,001	±0,0003/0,001	±0,0001/0,001	Ø 90	CTE6.1	1 unit(s)
HR-100AZ (W)	102	0,0001	±0,0002	±0,0001	Ø 90	CTE7.1	1 unit(s)
HR-150AZ (W)	152	0,0001	±0,0002	±0,0001	Ø 90	CTE8.1	1 unit(s)
HR-250AZ (W)	252	0,0001	±0,0003	±0,0002	Ø 90	CTE9.1	1 unit(s)

Алматы (7273)495-231
 Ангaрск (3955)60-70-56
 Архангельск (8182)63-90-72
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Благовещенск (4162)22-76-07
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Владикавказ (8672)28-90-48
 Владимир (4922)49-43-18
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
 Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Коломна (4966)23-41-49
 Кострома (4942)77-07-48
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Курган (3522)50-90-47
 Липецк (4742)52-20-81

Россия (495)268-04-70

Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Ноябрьск (3496)41-32-12
 Новосибирск (383)227-86-73
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16
 Петрозаводск (8142)55-98-37
 Псков (8112)59-10-37
 Пермь (342)205-81-47

Казахстан (772)734-952-31

Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Саратов (8342)22-96-24
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13
 Сыктывкар (8212)25-95-17
 Тамбов (4752)50-40-97
 Тургут (3462)77-98-35
 Тверь (4822)63-31-35

Киргизия (996)312-96-26-47

Тольятти (8482)63-91-07
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Улан-Удэ (3012)59-97-51
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Чебоксары (8352)28-53-07
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Чита (3022)38-34-83
 Якутск (4112)23-90-97
 Ярославль (4852)69-52-93